



PRESTAZIONI / PERFORMANCES

STACK	OUTPUT POWER	INPUT POWER	INSULATION CLASS	POLI	SPEED	ROOM TEMPERATURE
P. mm	W. Resi	W.Assorbiti	Classe.Isol.	Poli	Velocità	T.Ambiente
18	14/18	60/80	B/F	2	1/4	-10°+50°
20	15/20	70/90	B/F	2	1/4	-10°+50°
23	18/22	80/100	B/F	2	1/4	-10°+50°
25	20/26	90/120	B/F	2	1/4	-10°+50°
27	22/33	100/130	B/F	2	1/4	-10°+50°
30	24/36	110/140	B/F	2	1/4	-10°+50°
33	30/38	120/150	B/F	2	1/4	-10°+50°
37	32/40	130/160	B/F	2	1/4	-10°+50°
40	34/42	140/160	B/F	2	1/4	-10°+50°
45	36/46	150/180	B/F	2	1/4	-10°+50°
50	44/58	180/220	B/F	2	1/4	-10°+50°
60	50/62	190/240	B/F	2	1/4	-10°+50°
VOLTAGE		FREQUENCY		AXLE DIAMETER		
V. DA 100 A 240		Hz. DA 50 A 60		Diametro Asse 5		